

MASONS

PlastaSeal




MASONS PlastaSeal has been specifically formulated as a surface preparation for use with cement based plaster. MASONS PlastaSeal acts as an adhesion promoter and porosity equalizer. These features lessen water uptake leading to longer working time and less wastage.

USES:

MASONS PlastaSeal's unique structure imparts the above benefits to clay bricks, fibre-cement sheets, concrete tilt panel and gib board. It may be used on both exterior and interior work.

PREPARATION:

Ensure that all surfaces are clean, dry and free of dust and loose particles of plaster and cement. MASONS PlastaSeal cleans up with fresh water.

APPLICATION:	BRUSH	ROLLER
<p>May be applied by brush or roller although spray application by back pack or LVHP airless is recommended. Apply at 12-15m² per litre. Care should be taken to ensure overspray does not settle onto glass or aluminium sidings and doors. Allow at least 30 minutes drying before applying plaster or mortar and at least 60 minutes before painting.</p>		
		<h3 data-bbox="1248 1411 1529 1452">SPRAY UNIT</h3> 

PACKAGING:

MASONS PlastaSeal is available in 5 litre, 20 litre and 200 litre containers

PRECAUTIONS:

Do not apply in damp conditions or when temperature is below 10°C. If using PlastaSeal as a sealer over new plaster prior to painting allow at least 7 days curing of the plaster prior to painting.

TECHNICAL SERVICE:

For your nearest stockist or additional technical information on MASONS products and our wide range of sealing compounds, concrete admixtures and additives for the construction industry, contact MASONS on 0800 522 533.

The above information is based on our best knowledge and presented in good faith and we believe it to be true and accurate, however, due to the variable nature of application the suitability of the product for the intended use is the sole responsibility of the user.



MASONS |

12c Te Kea Place, Albany |

Freephone 0800 522 533